



TECHNICAL DATA - SEASON 2018 - 2019



Model

Chassis	Weight OPT	GLAMYS 326			GLAMYS 322			MC4 331			MC4 339			MC4 360			MC4 367		
		FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet		
Power HP		130	150	180	130	150	180	130	150	180	130	150	180	130	150	180	130	150	180
Power Kw		96	110	130	96	110	130	96	110	130	96	110	130	96	110	130	96	110	130
Maximum permissible mass kg (*)		3500			3500			3500			3500			3500			3500		
Total mass in running order kg		2992			2907			2913			3007			3057			3077		
Max. user payload kg.		508			593			587			493			443			423		
Maximum permissible mass kg (*)		3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850		
Total mass in running order kg		3057 / 3057			3013 / 3013			2913 / 2913			3007 / 3007			3057 / 3057			3077 / 3077		
Max. user payload kg.		593 / 793			637 / 837			737 / 937			643 / 843			593 / 793			573 / 773		
max. Towing capacity kg (braked)		2000			2000			2000			2000			2000			2000		
Maximum allowed mass kg (chassis Heavy 130cv/150-180cv)		4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400		
Number of beds		6			7			4			4			4			4		
Addition of the 5th bed		-----			-----			-----			-----			Opt			Opt		
Approved seats (3500 kg)		6			7			4			4			5			5		
Approved seats (3650 kg)		6			7			4			4			5			5		
Approved seats (3850 kg)		6			7			4			4			5			5		
5th homologated seat in running order		-----			-----			-----			-----			-----			-----		
Centralized locking cabin body with remote control		Opt			Opt			Opt			Opt			Opt			Opt		
Heated windshield (only MOTORHOME)	1 kg	-----			-----			-----			-----			-----			-----		
TECHNOTRIM LEVEL (silver dashboard)	1 kg	Opt			Opt			Opt			Opt			Opt			Opt		
LOUNGETRIM LEVEL (bronze dashboard)	1 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Manual cab air conditioning		STD			STD			STD			STD			STD			STD		
Automatic cab air conditioning		Opt			Opt			Opt			Opt			Opt			Opt		
Automatic gear box	18 kg	Opt			Opt			Opt			Opt			Opt			Opt		
LED DRL	0,5 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Alloy wheels 15 "	3 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Alloy wheels 16 "	3 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Steel wheels 16 "(Std. On chasis Heavy)	3 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Rear parking sensors	2 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Swivel cab seats		-----			-----			STD			STD			STD			STD		
Cab seat covers	3 kg	STD			STD			STD			STD			STD			STD		
Fresh water tank Lt. (total capacity when stopped)		110 Lit.			118 Lit.			115 Lit.			115 Lit.			100 Lit.			115 Lit.		
Fresh water tank Lt. (total capacity when on the way) **		20 Lit.			20 Lit.			20 Lit.			20 Lit.			20 Lit.			20 Lit.		
Waste water tank - Lt.		100 Lit.			100 Lit.			100 Lit.			100 Lit.			100 Lit.			100 Lit.		
Winter Pack ***	4 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Three-way fridge L.		150 Lit.			150 Lit.			142 Lit.			142 Lit.			142 Lit.			150 Lit.		
Oven	14 kg	Opt			Opt			Opt			Opt			Opt			Opt		
The new digital control panel Truma CP plus	0,2 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Heating system / Heater with air ventilation		Combi 4			Combi 4			Combi 4			Combi 4			Combi 4			Combi 4		
Heating system COMBI Diesel/COMBI EH	2 kg	Opt			Opt			Opt			Opt			Opt			Opt		
ALDE Heating	60 kg	-----			-----			-----			-----			-----			-----		
Heated floor	7 kg	Opt			Opt			Opt			Opt			Opt			Opt		
Sky-Dome on cabin roof	11 kg	-----			-----			STD			STD			STD			STD		
Rooflight living area																			

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

Chassis	MC4			MC4			MC4			MC4			NEVIS			NEVIS		
	373			375			379			381			373			375		
	FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet		
Power HP	130	150	180	130	150	180	130	150	180	130	150	180	130	150	180	130	150	180
Power Kw	96	110	130	96	110	130	96	110	130	96	110	130	96	110	130	96	110	130
Maximum permissible mass kg (*)	3500			3500			3500			3500			3500			3500		
Total mass in running order kg	3072			3072			3072			3157			3072			3072		
Max. user payload kg.	428			428			428			343			428			428		
Maximum permissible mass kg (*)	3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850		
Total mass in running order kg	3163 / 3163			3163 / 3163			3163 / 3163			3163 / 3163			3163 / 3163			3163 / 3163		
Max. user payload kg.	487 / 687			487 / 687			487 / 687			487 / 687			487 / 687			487 / 687		
max. Towing capacity kg (braked)	2000			2000			2000			2000			2000			2000		
Maximum allowed mass kg (chassis Heavy 130cv/150-180cv)	4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400		
Number of beds	4			4			4			4			4			4		
Addition of the 5th bed	Opt			Opt			Opt			-----			Opt			Opt		
Approved seats (3500 kg)	5			5			5			4			5			5		
Approved seats (3650 kg)	5			5			5			4			5			5		
Approved seats (3850 kg)	5			5			5			4			5			5		
5th homologated seat in running order	-----			-----			-----			-----			-----			-----		
Centralized locking cabin body with remote control	Opt			Opt			Opt			Opt			Opt			Opt		
Heated windshield (only MOTORHOME)	-----			-----			-----			-----			Opt			Opt		
TECHNOTRIM LEVEL (silver dashboard)	Opt			Opt			Opt			Opt			Opt			Opt		
LOUNGETRIM LEVEL (bronze dashboard)	Opt			Opt			Opt			Opt			Opt			Opt		
Manual cab air conditioning	STD			STD			STD			STD			STD			STD		
Automatic cab air conditioning	Opt			Opt			Opt			Opt			Opt			Opt		
Automatic gear box	Opt			Opt			Opt			Opt			Opt			Opt		
LED DRL	Opt			Opt			Opt			Opt			STD			STD		
Alloy wheels 15 "	Opt			Opt			Opt			Opt			Opt			Opt		
Alloy wheels 16 "	Opt			Opt			Opt			Opt			Opt			Opt		
Steel wheels 16 "(Std. On chasis Heavy)	Opt			Opt			Opt			Opt			Opt			Opt		
Rear parking sensors	Opt			Opt			Opt			Opt			Opt			Opt		
Swivel cab seats	STD			STD			STD			STD			STD			STD		
Cab seat covers	STD			STD			STD			STD			-----			-----		
Fresh water tank Lt. (total capacity when stopped)	115 Lit.			115 Lit.			115 Lit.			100 Lit.			115 Lit.			115 Lit.		
Fresh water tank Lt. (total capacity when on the way) **	20 Lit.			20 Lit.			20 Lit.			20 Lit.			20 Lit.			20 Lit.		
Waste water tank - Lt.	135 Lit.			135 Lit.			135 Lit.			135 Lit.			135 Lit.			225 Lit.		
Winter Pack ***	Opt			Opt			Opt			Opt			Opt			Opt		
Three-way fridge L.	150 Lit.			150 Lit.			150 Lit.			150 Lit.			150 Lit.			150 Lit.		
Oven	Opt			Opt			Opt			Opt			Opt			Opt		
The new digital control panel Truma CP plus	Opt			Opt			Opt			Opt			Opt			Opt		
Heating system / Heater with air ventilation	Combi 4			Combi 4			Combi 4			Combi 4			Combi 4			Combi 4		
Heating system COMBI Diesel/COMBI EH	Opt			Opt			Opt			Opt			Opt			Opt		
ALDE Heating	-----			-----			-----			-----			-----			-----		
Heated floor	Opt			Opt			Opt			Opt			Opt			Opt		
Sky-Dome on cabin roof	STD			STD			STD			STD			-----			-----		
Rooflight living area																		

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

Chassis	NEVIS 379			NEVIS 381		
	FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 35 / 36,5 Light		
Power HP	130	150	180	130	150	180
Power Kw	96	110	130	96	110	130
Maximum permissible mass kg (*)	3500			3500		
Total mass in running order kg	3072			3157		
Max. user payload kg.	428			343		
Maximum permissible mass kg (*)	3650 / 3850			3650 / 3850		
Total mass in running order kg	3163 / 3163			3163 / 3163		
Max. user payload kg.	487 / 687			487 / 687		
max. Towing capacity kg (braked)	2000			2000		
Maximum allowed mass kg (chassis Heavy 130cv/150-180cv)	4250 / 4400			4250 / 4400		
Number of beds	4			4		
Addition of the 5th bed	Opt			-----		
Approved seats (3500 kg)	5			4		
Approved seats (3650 kg)	5			4		
Approved seats (3850 kg)	5			4		
5th homologated seat in running order	-----			-----		
Centralized locking cabin body with remote control	Opt			Opt		
Heated windshield (only MOTORHOME)	Opt			Opt		
TECHNOTRIM LEVEL (silver dashboard)	Opt			Opt		
LOUNGETRIM LEVEL (bronze dashboard)	Opt			Opt		
Manual cab air conditioning	STD			STD		
Automatic cab air conditioning	Opt			Opt		
Automatic gear box	Opt			Opt		
LED DRL	STD			STD		
Alloy wheels 15 "	Opt			Opt		
Alloy wheels 16 "	Opt			Opt		
Steel wheels 16 "(Std. On chasis Heavy)	Opt			Opt		
Rear parking sensors	Opt			Opt		
Swivel cab seats	STD			STD		
Cab seat covers	-----			-----		
Fresh water tank Lt. (total capacity when stopped)	115 Lit.			100 Lit.		
Fresh water tank Lt. (total capacity when on the way) **	20 Lit.			20 Lit.		
Waste water tank - Lt.	135 Lit.			135 Lit.		
Winter Pack ***	Opt			Opt		
Three-way fridge L.	150 Lit.			150 Lit.		
Oven	Opt			Opt		
The new digital control panel Truma CP plus	Opt			Opt		
Heating system / Heater with air ventilation	Combi 4			Combi 4		
Heating system COMBI Diesel/COMBI EH	Opt			Opt		
ALDE Heating	-----			-----		
Heated floor	Opt			Opt		
Sky-Dome on cabin roof	-----			-----		
Rooflight living area						

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

Chassis	Weight OPT	GLAMYS	GLAMYS	MC4	MC4	MC4	MC4
		326	322	331	339	360	367
		FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet
Front transparent rooflight (40x40 cm)		-----	-----	-----	-----	-----	-----
Front transparent rooflight (40x40 cm) / drop-down bed		-----	-----	-----	-----	-----	-----
Front Rooflight MIDI-HEKI, (50x70 cm)	8 kg	STD	STD	-----	-----	-----	-----
Front Rooflight HEKI III (60x90 cm)	6 kg	-----	-----	-----	-----	-----	-----
Rooflight Kitchen area							
Transparent rooflight (40x40 cm) (kitchen area)		STD	STD	STD	STD	STD	STD
Turbovent (40 x 40 cm) (kitchen area)	1 kg	Opt	Opt	Opt	Opt	Opt	Opt
Rooflight in the Bathroom							
Transparent rooflight (28x28 cm) (bathroom)		-----	-----	-----	-----	-----	-----
Rear Rooflight							
Rear transparent rooflight (40x40 cm)		STD	STD	STD	STD	STD	STD
Rear Rooflight MIDI-HEKI, (50x70 cm)	8 kg	-----	-----	-----	-----	-----	-----
Rear Rooflight HEKI 3 (60x90 cm)	6 kg	Opt	-----	Opt	Opt	Opt	Opt
TV plate	4 kg	STD	STD	STD	STD	STD	STD
Matress cover	2 kg	Opt	Opt	Opt	Opt	Opt	Opt
Cab folding bed		-----	-----	-----	-----	-----	-----
Front Electric drop-down bed		-----	-----	STD	STD	STD	STD
Beds with orthopedic staves (Cab folding/drop-down bed/rear bed)		STD / ----- /-----	STD / ----- /-----	---/STD/STD	---/STD/STD	---/STD/STD	---/STD/STD
Rear bed manually adjustable		Opt	-----	-----	-----	STD	STD
Entrance door with mosquito net, window and dustbin		STD	STD	STD	STD	STD	STD
Carpet living area	7 kg	Opt	Opt	Opt	Opt	Opt	Opt
Insulation entrance step	4 kg	Opt	Opt	Opt	Opt	Opt	Opt
Cab pleated mats (A-Class)	8 kg	Opt	Opt	Opt	Opt	Opt	Opt
COLD KIT (Outside mats for cabin + dashboard mats)	8 kg	Opt	Opt	Opt	Opt	Opt	Opt
Solar Panel 120W + REGULATOR	11 kg	Opt	Opt	Opt	Opt	Opt	Opt
Pres-setting for rear-camera / Rear camera	1 kg	Std / Opt	Std / Opt	Std / Opt	Std / Opt	Std / Opt	Std / Opt

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	MC4	MC4	MC4	MC4	NEVIS	NEVIS
	373	375	379	381	373	375
Chassis	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet
Front Transparent rooflight (40x40 cm)	-----	-----	-----	-----	-----	-----
Front transparent rooflight (40x40 cm) / drop-down bed	-----	-----	-----	-----	-----	-----
Front Rooflight MIDI-HEKI, (50x70 cm)	-----	-----	-----	-----	STD	STD
Front Rooflight HEKI III (60x90 cm)	-----	-----	-----	-----	Opt	Opt
Rooflight Kitchen area						
Transparent rooflight (40x40 cm) (kitchen area)	STD	STD	STD	STD	STD	STD
Turbovent (40 x 40 cm) (kitchen area)	Opt	Opt	Opt	Opt	Opt	Opt
Rooflight in the Bathroom						
Transparent rooflight (28x28 cm) (bathroom)	-----	-----	-----	-----	-----	-----
Rear Rooflight						
Rear transparent rooflight (40x40 cm)	STD	STD	STD	STD	STD	STD
Rear Rooflight MIDI-HEKI, (50x70 cm)	-----	-----	-----	-----	-----	-----
Rear Rooflight HEKI 3 (60x90 cm)	Opt	Opt	Opt	Opt	Opt	Opt
TV plate	STD	STD	STD	STD	STD	STD
Matress cover	Opt	Opt	Opt	Opt	Opt	Opt
Cab folding bed	-----	-----	-----	-----	-----	-----
Front Electric drop-down bed	STD	STD	STD	STD	-----	-----
Beds with orthopedic staves (Cab folding/drop-down bed/rear bed)	---/STD/STD	---/STD/STD	---/STD/STD	---/STD/---	---/STD/STD	---/STD/STD
Rear bed manually adjustable	-----	-----	STD	STD	-----	-----
Entrance door with mosquito net, window and dustbin	STD	STD	STD	STD	STD	STD
Carpet living area	Opt	Opt	Opt	Opt	Opt	Opt
Insulation entrance step	Opt	Opt	Opt	Opt	Opt	Opt
Cab pleated mats (A-Class)	Opt	Opt	Opt	Opt	STD	STD
COLD KIT (Outside mats for cabin + dashboard mats)	Opt	Opt	Opt	Opt	Opt	Opt
Solar Panel 120W + REGULATOR	Opt	Opt	Opt	Opt	Opt	Opt
Pres-setting for rear-camera / Rear camera	Std / Opt	Std / Opt	Std / Opt	Std / Opt	Std / Opt	Std / Opt

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	NEVIS 379	NEVIS 381
Chassis	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 35 / 36,5 Light
Front Transparent rooflight (40x40 cm)	-----	-----
Front transparent rooflight (40x40 cm) / drop-down bed	-----	-----
Front Rooflight MIDI-HEKI, (50x70 cm)	STD	STD
Front Rooflight HEKI III (60x90 cm)	Opt	Opt
Rooflight Kitchen area		
Transparent rooflight (40x40 cm) (kitchen area)	STD	STD
Turbovent (40 x 40 cm) (kitchen area)	Opt	Opt
Rooflight in the Bathroom		
Transparent rooflight (28x28 cm) (bathroom)	-----	-----
Rear Rooflight		
Rear transparent rooflight (40x40 cm)	STD	STD
Rear Rooflight MIDI-HEKI, (50x70 cm)	-----	-----
Rear Rooflight HEKI 3 (60x90 cm)	Opt	Opt
TV plate	STD	STD
Matress cover	Opt	Opt
Cab folding bed	-----	-----
Front Electric drop-down bed	-----	-----
Beds with orthopedic staves (Cab folding/drop-down bed/rear bed)	---/STD/STD	---/STD/STD
Rear bed manually adjustable	STD	STD
Entrance door with mosquito net, window and dustbin	STD	STD
Carpet living area	Opt	Opt
Insulation entrance step	Opt	Opt
Cab pleated mats (A-Class)	STD	STD
COLD KIT (Outside mats for cabin + dashboard mats)	Opt	Opt
Solar Panel 120W + REGULATOR	Opt	Opt
Pres-setting for rear-camera / Rear camera	Std / Opt	Std / Opt

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	Weight OPT	GLAMYS			GLAMYS			GLAMYS			GLAMYS			MC4		
		822			826			840			823			822		
Chassis		FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet		
Power HP		130	150	180	130	150	180	130	150	180	130	150	180	130	150	180
Power Kw		96	110	130	96	110	130	96	110	130	96	110	130	96	110	130
Maximum permissible mass kg (*)		3500			3500			3500			3500			3500		
Total mass in running order kg		2903			2992			2992			3073			2992		
Max. user payload kg.		597			508			508			427			508		
Maximum permissible mass kg (*)		3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850		
Total mass in running order kg		3013 / 3013			3057 / 3057			3107 / 3107			3163 / 3163			3007 / 3007		
Max. user payload kg.		637 / 837			593 / 793			543 / 743			487 / 687			643 / 843		
max. Towing capacity kg (braked)		2000			2000			2000			2000			2000		
Maximum allowed mass kg (chassis Heavy 130cv/150-180cv)		4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400		
Number of beds		7			6			6			6			6		
Approved seats (3500 kg)		7			6			6			5			6		
Approved seats (3650 kg)		7			6			6			5			6		
Approved seats (3850 kg)		7			6			6			5			6		
5th homologated seat in running order		-----			-----			-----			-----			-----		
Centralized locking cabin body with remote control		STD			STD			STD			STD			STD		
Heated windshield (only MOTORHOME)	1 kg	-----			-----			-----			-----			-----		
TECHNOTRIM LEVEL (silver dashboard)	1 kg	Opt			Opt			Opt			Opt			Opt		
LOUNGETRIM LEVEL (bronze dashboard)	1 kg	Opt			Opt			Opt			Opt			Opt		
Manual cab air conditioning		STD			STD			STD			STD			STD		
Automatic cab air conditioning		Opt			Opt			Opt			Opt			Opt		
Automatic gear box	18 kg	Opt			Opt			Opt			Opt			Opt		
LED DRL	0,5 kg	Opt			Opt			Opt			Opt			Opt		
Alloy wheels 15 "	3 kg	Opt			Opt			Opt			Opt			Opt		
Alloy wheels 16 "	3 kg	Opt			Opt			Opt			Opt			Opt		
Steel wheels 16 "(Std. On chasis Heavy)	3 kg	Opt			Opt			Opt			Opt			Opt		
Rear parking sensors	2 kg	Opt			Opt			Opt			Opt			Opt		
Swivel cab seats		-----			-----			-----			STD			-----		
Cab seat covers	3 kg	STD			STD			STD			STD			STD		
Fresh water tank Lt. (total capacity when stopped)		125 Lit.			120 Lit.			120 Lit.			110 Lit.			125 Lit.		
Fresh water tank Lt. (total capacity when on the way) **		20 Lit.			20 Lit.			20 Lit.			20 Lit.			20 Lit.		
Waste water tank - Lt.		125 Lit.			100 Lit.			100 Lit.			100 Lit.			90 Lit.		
Winter Pack ***	4 kg	Opt			Opt			Opt			Opt			Opt		
Three-way fridge L.		150 Lit.			150 Lit.			150 Lit.			150 Lit.			150 Lit.		
Oven	14 kg	Opt			Opt			Opt			Opt			Opt		
The new digital control panel Truma CP plus	0,2 kg	Opt			Opt			Opt			Opt			Opt		
Heating system / Heater with air ventilation		Combi 4			Combi 4			Combi 4			Combi 4			Combi 4		
Heating system COMBI Diesel/COMBI EH	2 kg	Opt			Opt			Opt			Opt			Opt		
ALDE Heating	60 kg	-----			-----			-----			-----			-----		
Heated floor	7 kg	Opt			Opt			Opt			Opt			Opt		
Sky-Dome on cabin roof	11 kg	-----			-----			-----			-----			STD		

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	MC4			MC4			MC4			MC4			MC4		
	833			834			837			860			871		
Chassis	FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet		
Power HP	130	150	180	130	150	180	130	150	180	130	150	180	130	150	180
Power Kw	96	110	130	96	110	130	96	110	130	96	110	130	96	110	130
Maximum permissible mass kg (*)	3500			3500			3500			3500			3500		
Total mass in running order kg	2957			3007			3047			3057			3083		
Max. user payload kg.	543			493			453			443			417		
Maximum permissible mass kg (*)	3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850		
Total mass in running order kg	2957 / 2957			3007 / 3007			3047 / 3047			3057 / 3057			3083 / 3083		
Max. user payload kg.	693 / 893			643 / 843			603 / 803			593 / 793			567 / 767		
max. Towing capacity kg (braked)	2000			2000			2000			2000			2000		
Maximum allowed mass kg (chassis Heavy 130cv/150-180cv)	4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400		
Number of beds	5			4			4			5			4		
Approved seats (3500 kg)	5			4			4			5			4		
Approved seats (3650 kg)	5			4			4			5			4		
Approved seats (3850 kg)	5			4			4			5			4		
5th homologated seat in running order	-----			-----			-----			-----			-----		
Centralized locking cabin body with remote control	STD			STD			STD			STD			STD		
Heated windshield (only MOTORHOME)	-----			-----			-----			-----			-----		
TECHNOTRIM LEVEL (silver dashboard)	Opt			Opt			Opt			Opt			Opt		
LOUNGETRIM LEVEL (bronze dashboard)	Opt			Opt			Opt			Opt			Opt		
Manual cab air conditioning	STD			STD			STD			STD			STD		
Automatic cab air conditioning	Opt			Opt			Opt			Opt			Opt		
Automatic gear box	Opt			Opt			Opt			Opt			Opt		
LED DRL	Opt			Opt			Opt			Opt			Opt		
Alloy wheels 15 "	Opt			Opt			Opt			Opt			Opt		
Alloy wheels 16 "	Opt			-----			Opt			Opt			-----		
Steel wheels 16 "(Std. On chasis Heavy)	Opt			-----			Opt			Opt			-----		
Rear parking sensors	Opt			Opt			Opt			Opt			Opt		
Swivel cab seats	STD			STD			STD			STD			STD		
Cab seat covers	STD			STD			STD			STD			STD		
Fresh water tank Lt. (total capacity when stopped)	118 Lit.			118 Lit.			118 Lit.			118 Lit.			100 Lit.		
Fresh water tank Lt. (total capacity when on the way) **	20 Lit.			20 Lit.			20 Lit.			20 Lit.			20 Lit.		
Waste water tank - Lt.	90 Lit.			110 Lit.			90 Lit.			135 Lit.			135 Lit.		
Winter Pack ***	Opt			Opt			Opt			Opt			Opt		
Three-way fridge L.	150 Lit.			142 Lit.			150 Lit.			142 Lit.			142 Lit.		
Oven	Opt			Opt			Opt			Opt			Opt		
The new digital control panel Truma CP plus	Opt			Opt			Opt			Opt			Opt		
Heating system / Heater with air ventilation	Combi 4			Combi 4			Combi 4			Combi 4			Combi 4		
Heating system COMBI Diesel/COMBI EH	Opt			Opt			Opt			Opt			Opt		
ALDE Heating	-----			-----			-----			-----			-----		
Heated floor	Opt			Opt			Opt			Opt			Opt		
Sky-Dome on cabin roof	STD			STD			STD			STD			STD		

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	MC4			MC4			MC4			MC4			MC4		
	873			875			879			880			881		
Chassis	FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet		
Power HP	130	150	180	130	150	180	130	150	180	130	150	180	130	150	180
Power Kw	96	110	130	96	110	130	96	110	130	96	110	130	96	110	130
Maximum permissible mass kg (*)	3500			3500			3500			3500			3500		
Total mass in running order kg	3073			3073			3073			3073			3158		
Max. user payload kg.	427			427			427			427			342		
Maximum permissible mass kg (*)	3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850		
Total mass in running order kg	3163 / 3163			3163 / 3163			3163 / 3163			3163 / 3163			3163 / 3163		
Max. user payload kg.	487 / 687			487 / 687			487 / 687			487 / 687			487 / 687		
max. Towing capacity kg (braked)	2000			2000			2000			2000			2000		
Maximum allowed mass kg (chassis Heavy 130cv/150-180cv)	4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400		
Number of beds	5			5			5			5			4		
Approved seats (3500 kg)	5			5			5			5			4		
Approved seats (3650 kg)	5			5			5			5			4		
Approved seats (3850 kg)	5			5			5			5			4		
5th homologated seat in running order	-----			-----			-----			-----			-----		
Centralized locking cabin body with remote control	STD			STD			STD			STD			STD		
Heated windshield (only MOTORHOME)	-----			-----			-----			-----			-----		
TECHNOTRIM LEVEL (silver dashboard)	Opt			Opt			Opt			Opt			Opt		
LOUNGETRIM LEVEL (bronze dashboard)	Opt			Opt			Opt			Opt			Opt		
Manual cab air conditioning	STD			STD			STD			STD			STD		
Automatic cab air conditioning	Opt			Opt			Opt			Opt			Opt		
Automatic gear box	Opt			Opt			Opt			Opt			Opt		
LED DRL	Opt			Opt			Opt			Opt			Opt		
Alloy wheels 15 "	Opt			Opt			Opt			Opt			Opt		
Alloy wheels 16 "	Opt			Opt			Opt			-----			-----		
Steel wheels 16 "(Std. On chasis Heavy)	Opt			Opt			Opt			-----			-----		
Rear parking sensors	Opt			Opt			Opt			Opt			Opt		
Swivel cab seats	STD			STD			STD			STD			STD		
Cab seat covers	STD			STD			STD			STD			STD		
Fresh water tank Lt. (total capacity when stopped)	118 Lit.			118 Lit.			118 Lit.			118 Lit.			100 Lit.		
Fresh water tank Lt. (total capacity when on the way) **	20 Lit.			20 Lit.			20 Lit.			20 Lit.			20 Lit.		
Waste water tank - Lt.	135 Lit.			125 Lit.			135 Lit.			135 Lit.			135 Lit.		
Winter Pack ***	Opt			Opt			Opt			Opt			Opt		
Three-way fridge L.	150 Lit.			150 Lit.			150 Lit.			150 Lit.			150 Lit.		
Oven	Opt			Opt			Opt			Opt			Opt		
The new digital control panel Truma CP plus	Opt			Opt			Opt			Opt			Opt		
Heating system / Heater with air ventilation	Combi 4			Combi 4			Combi 4			Combi 4			Combi 4		
Heating system COMBI Diesel/COMBI EH	Opt			Opt			Opt			Opt			Opt		
ALDE Heating	Opt			Opt			-----			-----			-----		
Heated floor	Opt			Opt			Opt			Opt			Opt		
Sky-Dome on cabin roof	STD			STD			STD			STD			STD		

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	NEVIS			NEVIS			NEVIS			NEVIS		
	822			868			873			875		
Chassis	FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet			FIAT Ducato X290 cc.2300 Multijet		
Power HP	130	150	180	130	150	180	130	150	180	130	150	180
Power Kw	96	110	130	96	110	130	96	110	130	96	110	130
Maximum permissible mass kg (*)	3500			3500			3500			3500		
Total mass in running order kg	2989			3147			3158			3158		
Max. user payload kg.	511			353			342			342		
Maximum permissible mass kg (*)	3650 / 3850			3650 / 3850			3650 / 3850			3650 / 3850		
Total mass in running order kg	3123 / 3123			3147 / 3147			3163 / 3163			3163 / 3163		
Max. user payload kg.	527 / 727			503 / 703			487 / 687			487 / 687		
max. Towing capacity kg (braked)	2000			2000			2000			2000		
Maximum allowed mass kg (chassis Heavy 130cv/150-180cv)	4250 / 4400			4250 / 4400			4250 / 4400			4250 / 4400		
Number of beds	6			4			4			4		
Approved seats (3500 kg)	6			4			4			4		
Approved seats (3650 kg)	6			4			4			4		
Approved seats (3850 kg)	6			4			4			4		
5th homologated seat in running order	-----			-----			Opt (3650 kg)			Opt (3650 kg)		
Centralized locking cabin body with remote control	STD			STD			STD			STD		
Heated windshield (only MOTORHOME)	Opt			Opt			Opt			Opt		
TECHNOTRIM LEVEL (silver dashboard)	Opt			Opt			Opt			Opt		
LOUNGETRIM LEVEL (bronze dashboard)	Opt			Opt			Opt			Opt		
Manual cab air conditioning	STD			STD			STD			STD		
Automatic cab air conditioning	Opt			Opt			Opt			Opt		
Automatic gear box	Opt			Opt			Opt			Opt		
LED DRL	Opt			Opt			Opt			Opt		
Alloy wheels 15 "	Opt			Opt			Opt			Opt		
Alloy wheels 16 "	Opt			Opt			Opt			Opt		
Steel wheels 16 "(Std. On chasis Heavy)	Opt			Opt			Opt			Opt		
Rear parking sensors	Opt			Opt			Opt			Opt		
Swivel cab seats	STD			STD			STD			STD		
Cab seat covers	-----			-----			-----			-----		
Fresh water tank Lt. (total capacity when stopped)	110 Lit.			118 Lit.			118 Lit.			118 Lit.		
Fresh water tank Lt. (total capacity when on the way) **	20 Lit.			20 Lit.			20 Lit.			20 Lit.		
Waste water tank - Lt.	225 Lit.			135 Lit.			135 Lit.			225 Lit.		
Winter Pack ***	Opt			Opt			Opt			Opt		
Three-way fridge L.	150 Lit.			150 Lit.			150 Lit.			150 Lit.		
Oven	Opt			Opt			Opt			Opt		
The new digital control panel Truma CP plus	Opt			Opt			Opt			Opt		
Heating system / Heater with air ventilation	Combi 4			Combi 4			Combi 4			Combi 4		
Heating system COMBI Diesel/COMBI EH	Opt			Opt			Opt			Opt		
ALDE Heating	-----			-----			Opt			Opt		
Heated floor	Opt			Opt			Opt			Opt		
Sky-Dome on cabin roof	-----			-----			-----			-----		

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	NEVIS			NEVIS			NEVIS		
	879			880			882		
Chassis	FIAT Ducato X290 cc.2300 Multijet (Opt: AL-KO)			FIAT Ducato X290 35 / 36,5 Light			FIAT Ducato X290 35 / 36,5 Light		
Power HP	130	150	180	130	150	180	130	150	180
Power Kw	96	110	130	96	110	130	96	110	130
Maximum permissible mass kg (*)	3500			3500			3500		
Total mass in running order kg	3158			3158			3158		
Max. user payload kg.	342			342			342		
Maximum permissible mass kg (*)	3650 / 3850			3650 / 3850			3650 / 3850		
Total mass in running order kg	3163 / 3163			3163 / 3163			3163 / 3163		
Max. user payload kg.	487 / 687			487 / 687			487 / 687		
max. Towing capacity kg (braked)	2000			2000			2000		
Maximum allowed mass kg (chassis Heavy 130cv/150-180cv)	4250 / 4400			4250 / 4400			4250 / 4400		
Number of beds	4			4			4		
Approved seats (3500 kg)	4			4			4		
Approved seats (3650 kg)	4			4			4		
Approved seats (3850 kg)	4			4			4		
5th homologated seat in running order	Opt (3650 kg)			Opt (3650 kg)			-----		
Centralized locking cabin body with remote control	STD			STD			STD		
Heated windshield (only MOTORHOME)	Opt			Opt			Opt		
TECHNOTRIM LEVEL (silver dashboard)	Opt			Opt			Opt		
LOUNGETRIM LEVEL (bronze dashboard)	Opt			Opt			Opt		
Manual cab air conditioning	STD			STD			STD		
Automatic cab air conditioning	Opt			Opt			Opt		
Automatic gear box	Opt			Opt			Opt		
LED DRL	Opt			Opt			Opt		
Alloy wheels 15 "	Opt			Opt			Opt		
Alloy wheels 16 "	Opt			Opt			Opt		
Steel wheels 16 "(Std. On chasis Heavy)	Opt			Opt			Opt		
Rear parking sensors	Opt			Opt			Opt		
Swivel cab seats	STD			STD			STD		
Cab seat covers	-----			-----			-----		
Fresh water tank Lt. (total capacity when stopped)	118 Lit.			118 Lit.			100 Lit.		
Fresh water tank Lt. (total capacity when on the way) **	20 Lit.			20 Lit.			20 Lit.		
Waste water tank - Lt.	135 Lit.			135 Lit.			135 Lit.		
Winter Pack ***	Opt			Opt			Opt		
Three-way fridge L.	150 Lit.			150 Lit.			150 Lit.		
Oven	Opt			Opt			Opt		
The new digital control panel Truma CP plus	Opt			Opt			Opt		
Heating system / Heater with air ventilation	Combi 4			Combi 4			Combi 4		
Heating system COMBI Diesel/COMBI EH	Opt			Opt			Opt		
ALDE Heating	Opt			Opt			-----		
Heated floor	Opt			Opt			Opt		
Sky-Dome on cabin roof	-----			-----			-----		

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

		GLAMYS	GLAMYS	GLAMYS	GLAMYS	MC4
		822	826	840	823	822
Chassis	Weight OPT	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet
Rooflight living area						
Front Transparent rooflight (40x40 cm)		-----	-----	-----	-----	-----
Front transparent rooflight (40x40 cm) / drop-down bed		-----	-----	-----	-----	-----
Front Rooflight MIDI-HEKI, (50x70 cm)	8 kg	STD	STD	STD	STD	-----
Front Rooflight HEKI III (60x90 cm)	6 kg	-----	-----	-----	-----	-----
Rooflight Kitchen area						
Transparent rooflight (40x40 cm) (kitchen area)		-----	-----	-----	-----	-----
Turbovent (40 x 40 cm) (kitchen area)	1 kg	STD	STD	STD	STD	STD
Rooflight in the Bathroom						
Transparent rooflight (28x28 cm) (bathroom)		-----	-----	-----	-----	-----
Rear Rooflight						
Rear transparent rooflight (40x40 cm)		STD	STD	STD	STD	STD
Rear Rooflight MIDI-HEKI, (50x70 cm)	8 kg	-----	Opt	-----	-----	-----
Rear Rooflight HEKI 3 (60x90 cm)	6 kg	-----	-----	-----	-----	-----
TV plate	4 kg	STD	STD	STD	STD	STD
Matress cover	2 kg	Opt	Opt	Opt	Opt	Opt
Cab folding bed		-----	-----	-----	STD	-----
Front Electric drop-down bed		-----	-----	-----	-----	STD
Beds with orthopedic staves (Cab folding/drop-down bed/rear bed)		STD / ----- /-----	STD / ----- /-----	STD / ----- /-----	STD / ----- / STD	---/STD/STD
Rear bed manually adjustable		-----	-----	-----	-----	-----
Entrance door with mosquito net, window and dustbin		STD	STD	STD	STD	STD
Carpet living area	7 kg	Opt	Opt	Opt	Opt	Opt
Insulation entrance step	4 kg	Opt	Opt	Opt	Opt	Opt
Cab pleated mats (A-Class)	8 kg	Opt	Opt	Opt	Opt	Opt
COLD KIT (Outside mats for cabin + dashboard mats)	8 kg	Opt	Opt	Opt	Opt	Opt
Solar Panel 120W + REGULATOR	11 kg	Opt	Opt	Opt	Opt	Opt
Pres-setting for rear-camera / Rear camera	1 kg	Std / Opt	Std / Opt	Std / Opt	Std / Opt	Std / Opt

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

**) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	MC4	MC4	MC4	MC4	MC4
	833	834	837	860	871
Chassis	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet
Rooflight living area					
Front Transparent rooflight (40x40 cm)	-----	-----	-----	-----	-----
Front transparent rooflight (40x40 cm) / drop-down bed	-----	-----	-----	-----	-----
Front Rooflight MIDI-HEKI, (50x70 cm)	-----	-----	-----	-----	-----
Front Rooflight HEKI III (60x90 cm)	-----	-----	-----	-----	-----
Rooflight Kitchen area					
Transparent rooflight (40x40 cm) (kitchen area)	-----	-----	-----	-----	-----
Turbovent (40 x 40 cm) (kitchen area)	STD	STD	STD	STD	STD
Rooflight in the Bathroom					
Transparent rooflight (28x28 cm) (bathroom)	-----	-----	-----	-----	-----
Rear Rooflight					
Rear transparent rooflight (40x40 cm)	STD	STD	STD	STD	STD
Rear Rooflight MIDI-HEKI, (50x70 cm)	Opt	Opt	-----	Opt	Opt
Rear Rooflight HEKI 3 (60x90 cm)	-----	-----	-----	-----	-----
TV plate	STD	STD	STD	STD	STD
Matress cover	Opt	Opt	Opt	Opt	Opt
Cab folding bed	-----	-----	-----	-----	-----
Front Electric drop-down bed	STD	STD	STD	STD	STD
Beds with orthopedic staves (Cab folding/drop-down bed/rear bed)	---/STD/STD	---/STD/STD	---/STD/---	---/STD/STD	---/STD/STD
Rear bed manually adjustable	STD	-----	-----	STD	STD
Entrance door with mosquito net, window and dustbin	STD	STD	STD	STD	STD
Carpet living area	Opt	Opt	Opt	Opt	Opt
Insulation entrance step	Opt	Opt	Opt	Opt	Opt
Cab pleated mats (A-Class)	Opt	Opt	Opt	Opt	Opt
COLD KIT (Outside mats for cabin + dashboard mats)	Opt	Opt	Opt	Opt	Opt
Solar Panel 120W + REGULATOR	Opt	Opt	Opt	Opt	Opt
Pres-setting for rear-camera / Rear camera	Std / Opt	Std / Opt	Std / Opt	Std / Opt	Std / Opt

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	MC4	MC4	MC4	MC4	MC4
	873	875	879	880	881
Chassis	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet
Rooflight living area					
Front Transparent rooflight (40x40 cm)	-----	-----	-----	-----	-----
Front transparent rooflight (40x40 cm) / drop-down bed	-----	-----	-----	-----	-----
Front Rooflight MIDI-HEKI, (50x70 cm)	-----	-----	-----	-----	-----
Front Rooflight HEKI III (60x90 cm)	-----	-----	-----	-----	-----
Rooflight Kitchen area					
Transparent rooflight (40x40 cm) (kitchen area)	-----	-----	-----	-----	-----
Turbovent (40 x 40 cm) (kitchen area)	STD	STD	STD	STD	STD
Rooflight in the Bathroom					
Transparent rooflight (28x28 cm) (bathroom)	-----	-----	-----	-----	-----
Rear Rooflight					
Rear transparent rooflight (40x40 cm)	STD	STD	STD	STD	STD
Rear Rooflight MIDI-HEKI, (50x70 cm)	Opt	Opt	Opt	Opt	Opt
Rear Rooflight HEKI 3 (60x90 cm)	-----	-----	-----	-----	-----
TV plate	STD	STD	STD	STD	STD
Matress cover	Opt	Opt	Opt	Opt	Opt
Cab folding bed	-----	-----	-----	-----	-----
Front Electric drop-down bed	STD	STD	STD	STD	STD
Beds with orthopedic staves (Cab folding/drop-down bed/rear bed)	---/STD/STD	---/STD/STD	---/STD/STD	---/STD/STD	---/STD/STD
Rear bed manually adjustable	-----	-----	STD	STD	STD
Entrance door with mosquito net, window and dustbin	STD	STD	STD	STD	STD
Carpet living area	Opt	Opt	Opt	Opt	Opt
Insulation entrance step	Opt	Opt	Opt	Opt	Opt
Cab pleated mats (A-Class)	Opt	Opt	Opt	Opt	Opt
COLD KIT (Outside mats for cabin + dashboard mats)	Opt	Opt	Opt	Opt	Opt
Solar Panel 120W + REGULATOR	Opt	Opt	Opt	Opt	Opt
Pres-setting for rear-camera / Rear camera	Std / Opt	Std / Opt	Std / Opt	Std / Opt	Std / Opt

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	NEVIS	NEVIS	NEVIS	NEVIS
	822	868	873	875
Chassis	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet	FIAT Ducato X290 cc.2300 Multijet
Rooflight living area				
Front Transparent rooflight (40x40 cm)	-----	-----	-----	-----
Front transparent rooflight (40x40 cm) / drop-down bed	-----	-----	-----	-----
Front Rooflight MIDI-HEKI, (50x70 cm)	STD	STD	STD	STD
Front Rooflight HEKI III (60x90 cm)	Opt	Opt	Opt	Opt
Rooflight Kitchen area				
Transparent rooflight (40x40 cm) (kitchen area)	-----	-----	-----	-----
Turbovent (40 x 40 cm) (kitchen area)	STD	STD	STD	STD
Rooflight in the Bathroom				
Transparent rooflight (28x28 cm) (bathroom)	-----	-----	-----	-----
Rear Rooflight				
Rear transparent rooflight (40x40 cm)	STD	STD	STD	STD
Rear Rooflight MIDI-HEKI, (50x70 cm)	-----	Opt	Opt	Opt
Rear Rooflight HEKI 3 (60x90 cm)	-----	-----	-----	-----
TV plate	STD	STD	STD	STD
Matress cover	Opt	Opt	Opt	Opt
Cab folding bed	-----	-----	-----	-----
Front Electric drop-down bed	-----	-----	-----	-----
Beds with orthopedic staves (Cab folding/drop-down bed/rear bed)	---/STD/STD	---/STD/STD	---/STD/STD	---/STD/STD
Rear bed manually adjustable	-----	STD	-----	-----
Entrance door with mosquito net, window and dustbin	STD	STD	STD	STD
Carpet living area	Opt	Opt	Opt	Opt
Insulation entrance step	Opt	Opt	Opt	Opt
Cab pleated mats (A-Class)	STD	STD	STD	STD
COLD KIT (Outside mats for cabin + dashboard mats)	Opt	Opt	Opt	Opt
Solar Panel 120W + REGULATOR	Opt	Opt	Opt	Opt
Pres-setting for rear-camera / Rear camera	Std / Opt	Std / Opt	Std / Opt	Std / Opt

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



Model

	NEVIS	NEVIS	NEVIS
	879	880	882
Chassis	FIAT Ducato X290 cc.2300 Multijet (Opt: AL-KO)	FIAT Ducato X290 35 / 36,5 Light	FIAT Ducato X290 35 / 36,5 Light
Rooflight living area			
Front Transparent rooflight (40x40 cm)	-----	-----	-----
Front transparent rooflight (40x40 cm) / drop-down bed	-----	-----	-----
Front Rooflight MIDI-HEKI, (50x70 cm)	STD	STD	STD
Front Rooflight HEKI III (60x90 cm)	Opt	Opt	Opt
Rooflight Kitchen area			
Transparent rooflight (40x40 cm) (kitchen area)	-----	-----	-----
Turbovent (40 x 40 cm) (kitchen area)	STD	STD	STD
Rooflight in the Bathroom			
Transparent rooflight (28x28 cm) (bathroom)	-----	-----	-----
Rear Rooflight			
Rear transparent rooflight (40x40 cm)	STD	STD	STD
Rear Rooflight MIDI-HEKI, (50x70 cm)	Opt	Opt	Opt
Rear Rooflight HEKI 3 (60x90 cm)	-----	-----	-----
TV plate	STD	STD	STD
Matress cover	Opt	Opt	Opt
Cab folding bed	-----	-----	-----
Front Electric drop-down bed	-----	-----	-----
Beds with orthopedic staves (Cab folding/drop-down bed/rear bed)	---/STD/STD	---/STD/STD	---/STD/STD
Rear bed manually adjustable	STD	STD	STD
Entrance door with mosquito net, window and dustbin	STD	STD	STD
Carpet living area	Opt	Opt	Opt
Insulation entrance step	Opt	Opt	Opt
Cab pleated mats (A-Class)	STD	STD	STD
COLD KIT (Outside mats for cabin + dashboard mats)	Opt	Opt	Opt
Solar Panel 120W + REGULATOR	Opt	Opt	Opt
Pres-setting for rear-camera / Rear camera	Std / Opt	Std / Opt	Std / Opt

*) Calculated mass on light 130 hp

**) Pls. Check 20 lts. filling before driving

***) WINTER PACK : Insulated waste water tank and exhaust valve with antifreezing resistor



		MENFYS	MENFYS	MENFYS	MENFYS	MENFYS	MENFYS
	Weight OPT	VAN 1 S Line	VAN 1 Prestige	VAN 3 S Line	VAN 3 Prestige	VAN 4 CS S Line	VAN 4 CS Prestige
Chassis		Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato
Maximum technical permissible laden mass		3300 - 3500	3300 / 3500 (2,3 MJ)	3300 - 3500 - 3500H	3300 / 3500 (2,3 MJ)	3300 - 3500 - 3500H	3300 / 3500 (2,3 MJ)
Engine		2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ	2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ	2.0 MJ / 2.3 MJ / 2.3 MJ/ 2.3 MJ	2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ	2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ	2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ
Power		84 (115cv) / 96 (130cv)	84 (115cv) / 96 (130cv)	84 (115cv) / 96 (130cv) /	84 (115cv) / 96 (130cv)	84 (115cv) / 96 (130cv)	84 (115cv) / 96 (130cv) 110(150cv)/ 132(180cv)
Wheelbase		3450	3450	4035	4035	4035	4035
Number of gears (ratio numbers)		6 + RM	6 + RM	6 + RM	6 + RM	6 + RM	6 + RM
120L diesel tank		OPT / OPT / OPT	OPT / OPT / OPT	OPT / OPT / OPT	OPT / OPT / OPT	OPT / OPT / OPT	OPT / OPT / OPT
Tyres		R 15	R 15	R 15	R 15	R 15	R 15
Alloy wheels 15"	-6	OPT (3300)	OPT (3300)	OPT (3300)	OPT (3300)	OPT (3300)	OPT (3300)
Alloy wheels 16"	15	OPT (3500)	OPT (3500)	OPT (3500)	OPT (3500)	OPT (3500)	OPT (3500)
Fix & Go		STD / STD / STD	STD / STD / STD	STD / STD / STD	STD / STD / STD	STD / STD / STD	STD / STD / STD
MEASUREMENTS & WEIGHTS							
Maximum exterior dimensions MAX (length x width x height)		5420 / 2050 / 2650	5420 / 2050 / 2610	5995 / 2050 / 2650	5995 / 2050 / 2610	5995 / 2050 / 2650	5995 / 2050 / 2610
Maximum interior dimensions (length x width x height)		3100 / 1860 / 1890	3100 / 1860 / 1890	3685 / 1860 / 1890	3685 / 1860 / 1890	3685 / 1860 / 1890	3685 / 1860 / 1890
Weight in running conditions		2890 (2.0 MJ) 2905(2.3 MJ) 2905(33-35)	2890 (2.0 MJ) 2905(2.3 MJ)	2940 (2.0 MJ) / 2955 (2.3 MJ) 2955(33-35) 2995 (35H)	2940 (2.0 MJ) 2955 (2.3 MJ)	2975 (2.0 MJ-2.3 MJ) 3005 (2.3 MJ) 2975(33) 3005(35) 3045(35H)	2975 (2.0 MJ-2.3 MJ) 3005 (2.3 MJ)
Authorised towing weight		2000 (2.0 MJ) 2500 (2.3 MJ)	2000 (2.0 MJ) 2500 (2.3 MJ)	2000 (2.0 MJ) / 2500 (2.3 MJ)	2000 (2.0 MJ) 2500 (2.3 MJ)	2000 (2.0 MJ) 2500 (2.3 MJ)	2000 (2.0 MJ) 2500 (2.3 MJ)
SEATS							
Omologate seats (without / with motor bike rack)		4	4	4	4	4	4
Berths		2+1	2	2+1	3	2+1	3
KITCHEN							
Gas burners		2	2	2	2	2	2
Refrigerator (220V, 12V, gas)				80 L	80 L		
Refrigerator Compressor (220V, 12V)		85L	85L			85L	85L
GAS / WATER							
Clean water tank capacity (while driving) wastewater		90 / 90	90 / 90	100 / 90	100 / 90	90 / 90	100 / 90
Anti Freezing waste water pack	3	OPT	STD	OPT	STD	OPT	STD
Standard heater		Combi C4 (4000W)	COMBI 4	Combi C4 (4000W)	COMBI 4	Combi C4 (4000W)	COMBI 4
Combi control panel CP Plus	0	---	OPT	---	OPT	---	OPT
Gas Locher (2 x Max 7 kg EU)		STD	STD	STD	STD	STD	STD
EXTERNAL							
Electric step (width 550 mm)	11	OPT	STD	OPT	STD	OPT	STD
Roof-rack bar and ladder	6	OPT	OPT	OPT	OPT	OPT	OPT
Bicycle rack for 2 (max capacity 30 kg)	16	OPT	OPT	OPT	OPT	OPT	OPT
Tow hook (not fitted)	25	OPT	OPT	OPT	OPT	OPT	OPT
Metallized painted including front bumper & door handles (no for white version)	0	OPT	OPT	OPT	OPT	OPT	OPT
Roof light (400x400 mm)		2	1	2	1	2	1
Panoramic roof light (700x500 mm)	5	OPT	1	OPT	1	OPT	1
External light		---	STD	---	STD	---	STD



		MENFYS	MENFYS	MENFYS	MENFYS	MENFYS	MENFYS
	Weight OPT	VAN 1 S Line	VAN 1 Prestige	VAN 3 S Line	VAN 3 Prestige	VAN 4 CS S Line	VAN 4 CS Prestige
INSIDE							
Driver / passenger swivel seat bases		STD	STD	STD	STD	STD	STD
Bed slats in the rear bed		STD	STD	STD	STD	STD	STD
Cabin curtain		---	STD	---	STD	---	STD
TV cable		STD	STD	STD	STD	STD	STD
Seat covers & carpet for Fiat cab	3	OPT	OPT	OPT	OPT	OPT	OPT
Transversal bed in the seating	15	OPT	OPT	OPT	OPT	OPT	OPT
Carpet living area	6	OPT	OPT	OPT	OPT	OPT	OPT
Remis pleated mats	6	OPT	OPT	OPT	OPT	OPT	OPT
LCD TV Bracket	4	OPT	OPT	OPT	OPT	OPT	OPT
Roll-on curtains	2	---	OPT	---	OPT	---	OPT
Flynet for sliding door	4	OPT	OPT	OPT	OPT	OPT	OPT
Matress cover	1	OPT	OPT	OPT	OPT	OPT	OPT
Table extension	5	STD	STD	STD	STD	STD	STD
FEATURES							
Front bumper in white	0	OPT	STD	OPT	STD	OPT	STD
GOLDEN WHITE METALIZED colour varnish	0	OPT	OPT	OPT	OPT	OPT	OPT
ALUMINIUM GREY METALIZED colour varnish	0	OPT	OPT	OPT	OPT	OPT	OPT
ARTIC BLUE METALIZED colour varnish	0	OPT	OPT	OPT	OPT	OPT	OPT
IRON GREY METALIZED colour varnish	0	OPT	OPT	OPT	OPT	OPT	OPT
METALLIC BLACK METALIZED colour varnish		OPT	OPT	OPT	OPT	OPT	OPT
Automatic Air Conditioning	18	OPT	OPT	OPT	OPT	OPT	OPT
Automatic gear box	22	OPT	OPT	OPT	OPT	OPT	OPT
Fog lights	1	OPT	OPT	OPT	OPT	OPT	OPT
DRL LED	0	OPT	OPT	OPT	OPT	OPT	OPT



		MENFYS	MENFYS	MENFYS	MENFYS	MENFYS	MENFYS
	Weight OPT	VAN 3 MAXI S Line	VAN 3 MAXI Prestige	VAN 4 S Line	VAN 4 Prestige	VAN 5 S Line	VAN 5 Prestige
Chassis		Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato
Maximum technical permissible laden mass		3300 - 3500 - 3500H	3300 / 3500 (2,3 MJ)	3500 - 3500H	3500	3300 - 3500 - 3500H	3300 / 3500 (2,3 MJ)
Engine		2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ	2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ	2.3 MJ	2.3 MJ	2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ	2.0 MJ / 2.3 MJ 2.3 MJ/ 2.3 MJ
Power		84 (115cv) / 96 (130cv)	84 (115cv) / 96 (130cv)	96 (130cv) / 110(150cv)	96 (130cv) / 110(150cv)	96 (130cv) / 110(150cv)	84 (115cv) / 96 (130cv)
Wheelbase		4035	4035	4035	4035	4035	4035
Number of gears (ratio numbers)		6 + RM	5 + RM / 6 + RM	6 + RM	6 + RM	6 + RM	6 + RM
120L diesel tank		OPT / OPT / OPT	OPT / OPT / OPT	OPT	OPT / OPT	OPT / OPT / OPT	OPT / OPT / OPT
Tyres		R 15	R 15	R 15	R 15	R 15	R 15
Alloy wheels 15"	-6	OPT (3300)	OPT (3300)	---	---	OPT (3300)	OPT (3300)
Alloy wheels 16"	15	OPT (3500)	OPT (3500)	OPT (3500)	OPT (3500)	OPT (3500)	OPT (3500)
Fix & Go		STD / STD / STD	STD / STD / STD	STD	STD / STD	STD / STD / STD	STD / STD / STD
MEASUREMENTS & WEIGHTS							
Maximum exterior dimensions MAX (length x width x height)		5995 / 2050 / 2650	5995 / 2050 / 2610	6360 / 2050 / 2650	6360 / 2050 / 2610	5995 / 2050 / 2650	5995 / 2050 / 2610
Maximum interior dimensions (length x width x height)		3685 / 1860 / 1890	3685 / 1860 / 1890	4050 / 1860 / 1890	4050 / 1860 / 1890	3685 / 1860 / 1890	3685 / 1860 / 1890
Weight in running conditions		2960(2.0 MJ) 2975 (2.3 MJ) 2975(33-35) 3015(35H)	2960(2.0 MJ) 2975 (2.3 MJ)	3165 (2.3 MJ) 3165(35) 3170(35H)	3165 (2.3 MJ)	2970(33 2.0MJ) 2975 (33 2.3MJ) 2985 (35 2.3MJ) 2975(33) 2985(35) 3025(35H)	2970(33 2.0MJ) 2975 (33 2.3MJ) 2985 (35 2.3MJ)
Authorised towing weight		2000 (2.0 MJ) 2500 (2.3 MJ)	2000 (2.0 MJ) 2500 (2.3 MJ)	2500 (2.3 MJ)	2500 (2.3 MJ)	2000 (2.0 MJ) 2500 (2.3 MJ)	2000 (2.0 MJ) 2500 (2.3 MJ)
SEATS							
Omologate seats (without / with motor bike rack)		4	4	4	4	4	4
Berths		4+1	5	2+1	3	2+1	3
KITCHEN							
Gas burners		2	2	2	2	2	2
Refrigerator (220V, 12V, gas)		80 L	80 L	80 L	85 L	140 L	80 L
Refrigerator Compressor (220V, 12V)							
GAS / WATER							
Clean water tank capacity (while driving) wastewater		90 / 90	90 / 90	100 / 90	100 / 90	100 / 90	100 / 90
Anti Freezing waste water pack	3	OPT	STD	OPT	STD	OPT	STD
Standard heater		Combi C4 (4000W)	COMBI 4	Combi C4 (4000W)	COMBI 4	Combi C4 (4000W)	G (4000W)
Combi control panel CP Plus	0	---	OPT	---	OPT	---	OPT
Gas Locher (2 x Max 7 kg EU)		STD	STD	STD	STD	STD	STD
EXTERNAL							
Electric step (width 550 mm)	11	OPT	STD	OPT	STD	OPT	STD
Roof-rack bar and ladder	6	OPT	OPT	OPT	OPT	OPT	OPT
Bicycle rack for 2 (max capacity 30 kg)	16	OPT	OPT	OPT	OPT	OPT	OPT
Tow hook (not fitted)	25	OPT	OPT	OPT	OPT	OPT	OPT
Metallized painted including front bumper & door handles (no for white version)	0	OPT	OPT	OPT	OPT	OPT	OPT
Roof light (400x400 mm)		2	1	2	1	2	1
Panoramic roof light (700x500 mm)	5	OPT	1	OPT	1	OPT	1
External light		----	STD	---	STD	---	STD



		MENFYS	MENFYS	MENFYS	MENFYS	MENFYS	MENFYS
	Weight OPT	VAN 3 MAXI S Line	VAN 3 MAXI Prestige	VAN 4 S Line	VAN 4 Prestige	VAN 5 S Line	VAN 5 Prestige
INSIDE							
Driver / passenger swivel seat bases		STD	STD	STD	STD	STD	STD
Bed slats in the rear bed		STD	STD	STD	STD	STD	STD
Cabin curtain		---	STD	---	STD	---	STD
TV cable		STD	STD	STD	STD	STD	STD
Seat covers & carpet for Fiat cab	3	OPT	OPT	OPT	OPT	OPT	OPT
Transversal bed in the seating	15	OPT	OPT	OPT	OPT	OPT	OPT
Carpet living area	6	OPT	OPT	OPT	OPT	OPT	OPT
Remis pleated mats	6	OPT	OPT	OPT	OPT	OPT	OPT
LCD TV Bracket	4	OPT	OPT	OPT	OPT	OPT	OPT
Roll-on curtains	2	---	OPT	---	OPT	---	OPT
Flynet for sliding door	4	OPT	OPT	OPT	OPT	OPT	OPT
Matress cover	1	OPT	OPT	OPT	OPT	OPT	OPT
Table extension	5	STD	STD	STD	STD	STD	STD
FEATURES							
Front bumper in white	0	OPT	STD	OPT	STD	OPT	STD
GOLDEN WHITE METALIZED colour varnish	0	OPT	OPT	OPT	OPT	OPT	OPT
ALUMINIUM GREY METALIZED colourvarnish	0	OPT	OPT	OPT	OPT	OPT	OPT
ARTIC BLUE METALIZED colour varnish	0	OPT	OPT	OPT	OPT	OPT	OPT
IRON GREY METALIZED colour varnish	0	OPT	OPT	OPT	OPT	OPT	OPT
METALLIC BLACK METALIZED colour varnish		OPT	OPT	OPT	OPT	OPT	OPT
Automatic Air Conditioning	18	OPT	OPT	OPT	OPT	OPT	OPT
Automatic gear box	22	OPT	OPT	OPT	OPT	OPT	OPT
Fog lights	1	OPT	OPT	OPT	OPT	OPT	OPT
DRL LED	0	OPT	OPT	OPT	OPT	OPT	OPT

The masses indicated in this catalogue refer to the provisions of European Directive 2007/46/EC.

MASS IN RUNNING ORDER

It includes the weight of the empty BASE vehicle, of the driver (75 kg), 100% of the fuel (60-l tank), fresh water (tank filled with 20 l while travelling), and a gas tank for living purposes (20 kg). The mass in running order, and consequently the payload and/or certified seats may vary depending on the accessories installed.

PAYLOAD

This consists of the difference between the maximum technically permissible laden mass and the mass in running order. It includes elements for living purposes, the transported passengers defined by the manufacturer (driver excluded), and the personal effects. The payload calculation is based on the following parameters: 75 kg for each passenger (driver excluded), 10 kg of baggage for each passenger and for the driver, 10 kg for each metre of length of the vehicle, plus the remaining payload, which can be used for the installation of accessories or for additional baggage. All masses and loads of the empty vehicle have a tolerance of +/- 5%, in compliance with Directive 2007/46/EC. Any optional equipment increases the mass in running order and decreases the payload. The weight of non-standard accessories is not included in the mass in running order indicated in this catalogue. Additional accessories and devices reduce the payload by a quantity equal to their weight; the incidence of the weight of the individual accessories is shown in the special column in the technical data sheets or can be requested at our dealers. In case certain accessories are installed (for example, additional elements such as coupling device or motorbike rack), the mass of these accessories will affect the payload, possibly reducing it along with the number of certified seats. Please make sure that the maximum loads on the axles and the maximum technically permissible load mass are not exceeded during the complete loading phase of the vehicle. The regulations and requirements of each country may entail changes in the characteristics of this table. The number of certified seats may vary depending on the traffic regulations in force in each country.

NOTES

SEA S.P.A. – McLouis reserves itself the right to change the characteristics and the furnishings of all its models with no advance notice required; all data contained in this leaflet must therefore be considered approximate and non-binding. Despite thorough checks of the contents, we cannot exclude possible printing and/or translating errors. This catalogue does not constitute contractual documentation. Any reproduction, including in part, of the text or of the content of this document is prohibited. The indicated weights are exclusively approximated. Tolerances of +/- 5 % are allowed. Generally speaking, special equipment and options increase the no-load weight and entail a reduction in the payload. We hereby decline any and all responsibility in case structural changes are made to the vehicle; any assembly, disassembly or changes carried out by unauthorised workshops may jeopardise your safety and cause the warranty clauses to be forfeited. For additional information on installation and technical details, please contact one of our dealers.

GARAGE WEIGHT CAPACITY UP TO 300 KG

The load for the rear stowage has a maximum limit of 300 kg, uniformly distributed, in respect of the distribution of the maximum permissible loads on the front / rear axles.

